

## coupling for cable trays

|              |                 |                                |
|--------------|-----------------|--------------------------------|
| type number: | <b>KSBS 50</b>  | for width of cable tray 50 mm  |
|              | <b>KSBS 75</b>  | for width of cable tray 75 mm  |
|              | <b>KSBS 100</b> | for width of cable tray 100 mm |
|              | <b>KSBS 150</b> | for width of cable tray 150 mm |
|              | <b>KSBS 200</b> | for width of cable tray 200 mm |
|              | <b>KSBS 300</b> | for width of cable tray 300 mm |

for height of cable tray: 60 mm

length: 200 mm

thickness of metal sheet: 1,5 mm

product description: This cable coupling is suitable for connecting cable trays to create cable trays with maintained functionality during fires.

For connecting there are designed bolts NSM 6X10 (width 50-150 mm - 16 pcs; width 200-300 mm - 24 pcs). To protect the cables, the bolt head is inside the cable tray.

A bolt with a GMT surface finish is used for a tray with an F surface finish.

configuration: PO - Pre-Galvanized, zinc-layer 15 - 27 µm  
POF - Hot Dip Galvanized, zinc-layer 50 - 100 µm

sales amount: á 1 pc

certification: EN 61537:02

classification: ZP 27/2008 ..... P90-R  
DIN 41012-12 .... E90  
STN 92 0205 ..... PS 90

Fire classification is depend on the specific conditions of the cable tray, detailed in the catalog Systems with maintained functionality in fire

Systems may be supplied with various surface finishes whereas the surface finish does not affect the determined maintained time of operability in fire.

storage: EN 60721-3-1

