

item number	A	B	thickness of metal sheet	max. load (kg)	weight (kg/pc)
DZDS 100/B_S	150	85	1,5	70	0,25
DZDS 100/B_F					0,27
DZDS 150/B_S	200	85	1,5	60	0,26
DZDS 150/B_F					0,29
DZDS 200/B_S	250	85	1,5	60	0,38
DZDS 200/B_F					0,42
DZDS 300/B_S	350	85	2,0	60	0,66
DZDS 300/B_F					0,68
DZDS 400/B_S	450	85	2,0	60	0,80
DZDS 400/B_F					0,85
DZDS 500/B_S	550	122	2,0	60	1,01
DZDS 500/B_F					1,09
DZDS 600/B_S	650	122	2,0	60	1,11
DZDS 600/B_F					1,20



product description: The support is designed as a supporting structure for fixing wire trays to the wall.

Quick and reliable fixation of the wire tray to the bracket is secured by bending in the fastening tabs.

It is necessary to use a hanger DZZ/B, while the wire cable tray DZ 60X60 is installed on the wall.

surface finish: S - Pre-Galvanized, zinc-layer 15 - 27 µm
F - Hot Dip Galvanized, zinc-layer 45 µm (min. 35 µm)

sales amount: á 1 pc

storage: EN 60721-3-1

