


product description: intended for installation to the distribution of low voltage
designed for mounting on the floor
designed for load capacity common in apartments and offices

material: PVC - Pb-free
self-snuffing: yes, within 30 s
temperature resistance: -5 - +60 °C
flaming loop test: 850 °C
impact strength: 2 J
protection types: IP30
fire class for underlying material: A1-F
inside area: 170+360+170 mm²
distance base perforation: 200 ±20 mm
length tolerance: ±10 mm
weight: 0,44 kg/m
mechanical protection according to EN 50102: IK07
certification: EN 50085-1 ed.2:06, EN 50085-2-1:07
storage: ČSN 64 0090



usage of inner trunking cross-section (60%):	orientation cable diameter (mm)	6	7	8	8,5	9	9,5	10	11	12	13	14	15	16
	number of inserted cables	13	9	8	5	5	5	4	4	1	1	1	1	1

chemical resistance: YES: amoniak 25%, distilled water, ethanol 50%, sodium hydroxide 60%, hydrofluoric acid 40%, acetic acid 5%, sulfuric acid 96%, medicinal oil, methanol, olive oil, petroleum, hydrogen peroxide 20%, transformer oil, sodium carbonate
NO: aceton, benzen, chlorinated hydrocarbons, tetrachlorocarbon

item number	length	color (approximate)	package	package - description	note
LO 75_HD	2 m	white RAL 9003	28 m	carton	-
LO 75_P2	2 m	white RAL 9003	28 m	carton	self-adhesive tape
LO 75_KD	2 m	light gray (RAL 7035)	28 m	carton	-
LO 75_LD	2 m	dark gray (RAL 7012)	28 m	carton	-
LO 75_L2	2 m	dark gray (RAL 7012)	28 m	carton	self-adhesive tape
8873_HB		white RAL 9003	2 / 112 pcs	foil / carton	
8873_KB		light gray (RAL 7035)	2 / 110 pcs	foil / carton	bending
8873_LB		dark gray (RAL 7012)	2 / 110 pcs	foil / carton	
8874_HB		white RAL 9003	2 / 80 pcs	foil / carton	
8874_KB		light gray (RAL 7035)	2 / 100 pcs	foil / carton	branching
8874_LB		dark gray (RAL 7012)	2 / 150 pcs	foil / carton	