

| item number            | for width<br>of cable<br>tray | for height<br>of cable<br>tray | A   | thickness<br>of metal<br>sheet | weight<br>kg/ps | amount of<br>bolts for<br>connection |
|------------------------|-------------------------------|--------------------------------|-----|--------------------------------|-----------------|--------------------------------------|
| <b>NO 45X50X62_S</b>   | 62                            | 50                             | 125 | 0,7                            | 0,21            | 4                                    |
| <b>NO 45X50X62_F</b>   |                               |                                |     |                                | 0,23            |                                      |
| <b>NO 45X50X125_S</b>  | 125                           | 50                             | 151 | 0,7                            | 0,29            | 4                                    |
| <b>NO 45X50X125_F</b>  |                               |                                |     |                                | 0,33            |                                      |
| <b>NO 45X50X250_S</b>  | 250                           | 50                             | 203 | 0,7                            | 0,53            | 4                                    |
| <b>NO 45X50X250_F</b>  |                               |                                |     |                                | 0,69            |                                      |
| <b>NO 45X100X125_S</b> | 125                           | 100                            | 151 | 0,7                            | 0,45            | 8                                    |
| <b>NO 45X100X125_F</b> |                               |                                |     |                                | 0,48            |                                      |
| <b>NO 45X100X250_S</b> | 250                           | 100                            | 203 | 0,7                            | 0,69            | 8                                    |
| <b>NO 45X100X250_F</b> |                               |                                |     |                                | 0,89            |                                      |
| <b>NO 45X100X500_S</b> | 500                           | 100                            | 307 | 0,7                            | 1,43            | 8                                    |
| <b>NO 45X100X500_F</b> |                               |                                |     |                                | 1,88            |                                      |

**product description:** The elbow 45° is used to bend cable trays running through MARS cable trays by 45° in a horizontal direction.

To fix the connection use the bolt NSM 6X10. To protect the cables, the bolt head is inside the cable tray.

A bolt with a GMT surface finish is used for a tray with an F surface finish.

These items can also be ordered in a varnished version.

**surface finish:** S - Pre-Galvanized, zinc-layer 15 - 27 µm  
F - Hot Dip Galvanized, zinc-layer 45 µm (min. 35 µm)

**sales amount:** á 1 pc

**certification:** EN 61537:02

**storage:** EN 60721-3-1

