item number	for w idth of cable tray	for height of cable tray	A	thickness of metal sheet	w eight kg/ps	amount of bolts for connection
NO 45X50X62_S	62	50	125	0,7	0,21	4
NO 45X50X62_F					0,23	
NO 45X50X125_S	125	50	151	0,7	0,29	4
NO 45X50X125_F					0,33	
NO 45X50X250_S	250	50	203	0,7	0,53	4
NO 45X50X250_F					0,69	
NO 45X100X125_S	125	100	151	0,7	0,45	8
NO 45X100X125_F					0,48	
NO 45X100X250_S	250	100	203	0,7	0,69	8
NO 45X100X250_F					0,89	
NO 45X100X500_S	500	100	307	0,7	1,43	8
NO 45X100X500_F					1,88	



product description: The elbow 45° is used to bend cable trays running through MARS cable trays by 45° in a horizontal direction.

To fix the connection use the bolt NSM 6X10. To protect the cables, the bolt head is inside the cable tray.

A bolt with a GMT surface finish is used for a tray with an F surface finish.

These items can also be ordered in a varnished version.

surface finish: S - Pre-Galvanized, zinc-layer 15 - 27 µm
F - Hot Dip Galvanized, zinc-layer 45 µm (min. 35 µm)

sales amount: á 1 pc

certification: EN 61537:02

storage: EN 60721-3-1