

| item number            | for<br>width<br>of cable<br>tray | for<br>height<br>of cable<br>tray | A   | thickness<br>of metal<br>sheet | weight<br>kg/ps | amount of<br>bolts for<br>connection |
|------------------------|----------------------------------|-----------------------------------|-----|--------------------------------|-----------------|--------------------------------------|
| <b>NO 90X50X62_S</b>   | 62                               | 50                                | 222 | 0,7                            | 0,38            | 4                                    |
| <b>NO 90X50X62_F</b>   |                                  |                                   |     |                                | 0,45            |                                      |
| <b>NO 90X50X125_S</b>  | 125                              | 50                                | 285 | 0,7                            | 0,57            | 4                                    |
| <b>NO 90X50X125_F</b>  |                                  |                                   |     |                                | 0,67            |                                      |
| <b>NO 90X50X250_S</b>  | 250                              | 50                                | 410 | 0,7                            | 1,08            | 4                                    |
| <b>NO 90X50X250_F</b>  |                                  |                                   |     |                                | 1,44            |                                      |
| <b>NO 90X100X125_S</b> | 125                              | 100                               | 285 | 0,7                            | 0,80            | 8                                    |
| <b>NO 90X100X125_F</b> |                                  |                                   |     |                                | 0,94            |                                      |
| <b>NO 90X100X250_S</b> | 250                              | 100                               | 410 | 0,7                            | 1,38            | 8                                    |
| <b>NO 90X100X250_F</b> |                                  |                                   |     |                                | 1,84            |                                      |
| <b>NO 90X100X500_S</b> | 500                              | 100                               | 660 | 0,7                            | 2,59            | 8                                    |
| <b>NO 90X100X500_F</b> |                                  |                                   |     |                                | 3,47            |                                      |

product description: The elbow 90° is used to bend cable trays running through MARS cable trays by 90° in a horizontal direction.

For the elbows NO 90X100X500 the outer right angle of the side walls is replaced by skewed cut.

To fix the connection use the bolt NSM 6X10. To protect the cables, the bolt head is inside the cable tray.

A bolt with a GMT surface finish is used for a tray with an F surface finish.

These items can also be ordered in a varnished version.

surface finish: S - Pre-Galvanized, zinc-layer 15 - 27 µm  
F - Hot Dip Galvanized, zinc-layer 45 µm (min. 35 µm)

sales amount: á 1 pc

certification: EN 61537:02

storage: EN 60721-3-1

