



product
description:

the pipes are intended for installation to the distribution of low voltage
the pipes are suitable for mechanical protection of conductors and cables inside halls (indoor)
the pipes are made of galvanized steel bar at the top (zinc layer 3 - 4 μm) and isolation layer inside

material: steel

temperature resistance: -45 - +90 °C

mechanical resistance: 750 N / 5 cm

classification according to EN 61386-1 ed. 2: 33522

certification: EN 61386-1 ed.2:09, EN 61386-22:04

storage: EN 60721-3-1



accessories:

clamps: 3613 A_S, 3616 A_S, 3623 A_S, 3629 A_S, 3636 A_S, 3648 A_S

item number	dn outer Ø (mm)	di min. inner Ø (mm)	length = package (m)	package weight (kg)
3313_B	18,9	13,5	10	1,9
3313_XX	18,9	13,5	100	18,7
3316_B	21,4	16	10	2,3
3316_XX	21,4	16	100	23,5
3323_B	28,9	23	10	3,3
3323_XX	28,9	23	50	16,4
3329_B	35,2	29	10	4,5
3329_XX	35,2	29	50	22,3
3336_B	43	36	5	3,0
3336_XX	43	36	25	14,8
3348_B	54,9	48	5	3,7
3348_XX	54,9	48	25	18,3